

# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

# **MODEL G7213Z 24" PLANER 7-1/2 HP 3-PHASE**

Product Dimensions:	
Weight	
· ·	
Shipping Dimensions:	
Type	Wood Crate
* *	
<u>~</u>	
Electrical:	
Switch	Magnetic with Thermal Overload Protector
	220V
<del>-</del>	
<b>o</b>	
•	
•	P7213Z302A, 302B, 302C, 302D
Motors:	
Main	
Type	TEFC Induction
Horsepower	7-1/2 HP
Voltage	220/440V
Prewired	220V
Phase	Three
Amps	25/12.5A
Speed	3450 RPM
Cycle	60 Hz
· · · · · · · · · · · · · · · · · · ·	1
	Two Belt Drive
	Sealed and Lubricated
Feed	
Type	TEFC Induction
	2 HP
•	
Descripted	220\
	Three
	25/12.5A
	3450 RPM
•	
•	
	Variable Split Pulley System
Deanings	Sealed and Lubricated

## **Main Specifications:**

#### **Operation Info**

	Max. Cut Width	24 in
	Max. Cut Height	
	Min. Stock Length	
	Min. Stock Width	
	Max. Stock Thickness.	
	No. Of Cuts Per Inch.	
	No. Of Cuts Per Minute	
	Cutterhead Speed	
	Planing Feed Rate	
	Max. Cut Depth Planing Full Width	
	Max. Cut Depth Planing 6 Inch Wide Board	1/8 in.
Cut	tterhead Info	
	Cutterhead Type	4 Knife
	Cutterhead Dia	
	No. Of Knives	4
	Knife Type	HSS
	Knife Size Length	24 in.
	Knife Size Width	1 in.
	Knife Size Thickness	1/8 in.
	Knife Adjustment	Jack Screws
Tab	ole Info	
	Table Mayament	O in
	Table Movement	
	Table Bed Size Length	
	Table Bed Size Width	
	Table Bed Size Thickness	
	No. Of Bed Rollers	
	Floor To Table Height	24 - 33 in.
Cor	nstruction	
	Table Construction	Precision Ground Cast Iron
	Body Construction	
	Cutterhead Assembly Construction	
	Infeed Roller Construction	
	Outfeed Roller Construction	•
	Paint	
Oth	ner	
	Table Locks	One Positive
	Measurement Scale	
	No. Of Dust Ports.	
	Dust Port Size	
	Mobile Base	
	Wobile Dase	
Other Spe	ecifications:	
Coi	untry Of Origin	Taiwan
	rranty	
	rial Number Location	
		·
Ass	sembly Time	15 minutes

### Features:

Lever Control Bed Rollers
Segmented Chip Breaker and Infeed Roller
Table Locks
5" Collar Chip Chute
Variable Speed Feed